



A KEE SAFETY PRODUCT

SAFE RAPID ACCESS

Roofline System



- COST EFFECTIVE ALTERNATIVE TO SCAFFOLDING
- HEIGHT ADJUSTABLE IN SECONDS
- QUICK AND SIMPLE TO CONSTRUCT
- CONFORMS TO EN 13374 CLASS C AND EN 12811

Safe roof, fascia and wall access

The Roofline System is one or more Easi-Dec platforms linked securely with our Catwalk to form a continuous fully-guarded platform. Our Roofline System has been designed to provide simple, rapid access to roofline level, without the time constraints of erecting scaffolding. The 8 or 10 metre Roofline System comprises of 2 Easi-Dec platforms and a Catwalk and can be erected in less than 30 minutes. The use of telescopic legs gives height adjustment in 30 mm increments and can even cope with sloping ground. With a comprehensive range of accessories the Roofline System offers numerous benefits and is ready to overcome all kinds of challenging access situations. Whilst the standard leg height (3.3 m - 5.5 m) is sold as part of the system, alternative leg lengths are also available (see below) enabling you to cover the majority of properties, ranging from 2.34 m (typical bungalow) up to 6.8 m (2 storey town house).

Comprehensive Accessory Range

Catwalk: The lightweight aluminium staging is a standard 4m, but a 6m length is also available, and both are supplied with an integral handrail system and toe boards.

Rolling Window Bar: Available as an alternative to the standard wheels supplied with the Roofline System, the Rolling Window Bar provides a continuous platform support for load distribution.

End Support Frame: Where restricted access precludes the use of the standard 2 m Dec, a single leg support can be used. Designed to provide access where boundaries or projecting structures restrict normal platform use.

Stand-Off Kit: To enable access to or over deep soffits, the working platform can be fitted with a pair of 20 cm Stand-Off arms enabling the platform to be positioned away from the building. Safe working is maintained by the addition of front handrails and toe boards.

Corner Kit: To enable access to large box-end gutters, or to provide a continuous working platform around corners, the addition of a Corner Kit provides simple stable support. The corner leg is attached to the platform and secured with the addition of an adjustable brace, enabling the platform to project beyond the end of the structure. Prior to use, a full onsite risk assessment must be carried out, and in some circumstances the Easi-Dec must be tied into the structure.

Features

- No tools assembly feature
- Height adjustable in seconds
- Independently adjustable legs to cope with uneven or sloping ground
- Modular assembly to provide platforms 2, 8 or 10 m long
- Non-corrosive aluminium
- Lightweight and compact: easy storage and transportation

Benefits

- Cost effective alternative to scaffolding
- Quick and simple to construct
- Can easily span obstacles (eg. conservatories)
- Easy to store and transport
- Flexibility to quickly change work locations
- Long-life durability
- Compliant with EN13374 Class C and EN 12811

Accessories



Stand-Off Kit



Rolling Window Bar

TECHNICAL SPECIFICATION

Load rating	600 kg uniformly distributed
System weight	214 kg
Platform size	2 m x 800 mm wide
4 m Catwalk dimensions	600 mm x 4.600 mm
6 m Catwalk dimensions	600 mm x 6.600 mm
Material	High grade aluminium

LEG SPECIFICATION

Super Legs	4.50 m - 6.80 m platform height
Standard Legs	3.30 m - 5.50 m platform height
16' Legs	3.00 m - 4.75 m platform height
14' Legs	2.75 m - 4.15 m platform height
Bungalow Legs	2.34 m - 2.90 m platform height



KEE SAFETY LLC
Dubai Investment Park (DIP)
Near Green Community
PO Box 18448
Dubai, UAE

Tel: (+971) 4 8859066
Fax: (+971) 4 8859065
Email: uaesales@keesafety.com
Website: www.keesafety.ae